

EL[®]MARK

The Brand of Electricity

MOVEBLE LED SPOTLIGHTS EL-6453 SERIES

GENERAL INFORMATION »

- ∴ Rated voltage: 220-240V/ 50-60Hz
- ∴ Power: 12W; 20W
- ∴ Driver: non-isolated driver
- ∴ Colour temperature: 3000K; 4000K
- ∴ Colour body: White
- ∴ Material: Aluminium
- ∴ Beam angle: 38°
- ∴ CRI: Ra≥80
- ∴ UGR<19
- ∴ Power factor: 0.5
- ∴ Protection level against moisture and dust: IP44
- ∴ Available in variant with an emergency kit



FEATURES »

- ∴ Energy-saving fixture in replacement of fluorescent downlights
- ∴ Safety, low voltage operation
- ∴ Installation in suspended ceilings
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Modern luminaire designed for hotels, offices, conference halls, museums and restaurants.
- ∴ High degree of protection
- ∴ Lightweight construction

TECHNICAL SPECIFICATION SHEET



Honeycomb Anti-Glare

Energy class:



[PRODUCT DETAILS »](#)

Catalogue number	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height	Cut hole (mm)	Colour body
92EL64531230/WH	Recessed LED COB	12	900	3000	85	96	75	white
92EL64531240/WH	Recessed LED COB	12	900	4000	85	96	75	white
92EL64532030/WH	Recessed LED COB	20	1500	3000	110	110	100	white
92EL64532040/WH	Recessed LED COB	20	1500	4000	110	110	100	white

