



LUMINAIRE PHOTOMETRIC TEST REPORT

| | | |
|-----------------------------|-----------------|------------------|
| NAME: 95EL401524W/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: F320 x 55 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: round | Shielding Angle: |

| DATA OF LAMP | | PHOTOMETRIC DATA | | | |
|-------------------|----------------|------------------|--------|--------------------------|-----------|
| MODEL | 95EL401524W/GR | Imax (cd) | 793.3 | S/MH (C0/180) | 1.26 |
| NOMINAL POWER (W) | 24 | LOR (%) | 121.8 | S/MH (C90/270) | 1.26 |
| RATED VOLTAGE (V) | 230 | TOTAL FLUX (lm) | 2337.8 | η UP, DN (C0-180) | 0.0, 60.7 |
| NOMINAL FLUX (lm) | 1920 | CIE CLASS | DIRECT | η UP, DN (C180-360) | 0.0, 61.1 |
| LAMPS INSIDE | 1 | η up (%) | 0.0 | CIBSE SHR NOM | 1.25 |
| TEST VOLTAGE (V) | 230 | η down (%) | 121.8 | CIBSE SHR MAX | 1.35 |



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature: 25.3°C
Operators:
Test Date: 01 February 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.340m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

| γ | C0 | C45 | C90 | C135 | C180 | C225 | C270 | C315 | γ | Φ zone | Φ total | %lum, lamp |
|----------|-----------------------|-------|-------|-------|-------|-------|-------|-------|----------|-------------|--------------|------------|
| 10 | 778.1 | 777.2 | 777.1 | 778.8 | 780.4 | 780.9 | 780.6 | 779.2 | 0- 10 | 75.04 | 75.04 | 3.21,3.91 |
| 20 | 735.2 | 733.4 | 733.3 | 736.8 | 739.7 | 740.4 | 739.7 | 737.2 | 10- 20 | 214.9 | 289.9 | 12.4,15.1 |
| 30 | 667.1 | 664.9 | 664.5 | 669.3 | 673.7 | 674.1 | 672.8 | 669.3 | 20- 30 | 325.4 | 615.3 | 26.3,32 |
| 40 | 577.3 | 575.1 | 574.7 | 580.5 | 585.6 | 585.5 | 583.7 | 579.7 | 30- 40 | 392.4 | 1008 | 43.1,52.5 |
| 50 | 470.6 | 468.6 | 468.3 | 474.8 | 480.0 | 479.4 | 477.1 | 472.7 | 40- 50 | 407.9 | 1416 | 60.6,73.7 |
| 60 | 352.3 | 350.8 | 350.7 | 357.4 | 362.3 | 361.5 | 359.0 | 354.5 | 50- 60 | 371.9 | 1788 | 76.5,93.1 |
| 70 | 228.9 | 227.9 | 228.1 | 234.6 | 238.9 | 238.0 | 235.7 | 231.1 | 60- 70 | 291.6 | 2079 | 88.9,108 |
| 80 | 111.3 | 111.7 | 111.9 | 117.5 | 120.3 | 118.4 | 116.8 | 112.6 | 70- 80 | 182.2 | 2261 | 96.7,118 |
| 90 | 30.90 | 31.49 | 32.40 | 34.28 | 34.90 | 34.53 | 33.75 | 31.47 | 80- 90 | 76.40 | 2338 | 100,122 |
| 100 | | | | | | | | | 90-100 | | | |
| 110 | | | | | | | | | 100-110 | | | |
| 120 | | | | | | | | | 110-120 | | | |
| 130 | | | | | | | | | 120-130 | | | |
| 140 | | | | | | | | | 130-140 | | | |
| 150 | | | | | | | | | 140-150 | | | |
| 160 | | | | | | | | | 150-160 | | | |
| 170 | | | | | | | | | 160-170 | | | |
| 180 | | | | | | | | | 170-180 | | | |
| DEG | LUMINOUS INTENSITY:cd | | | | | | | | | UNIT:lm | | |

Conical surface Flux(90deg): 1213.1 lm

%lum = 51.9%

%lamp = 63.2%

Conical surface Flux(130deg): 1945.7 lm

%lum = 83.2%


%lamp = 101.3%

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature:25.3°C
 Operators:
 Test Date:01 February 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.340m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

| | | |
|-----------------------------|-----------------|------------------|
| NAME: 95EL401524W/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: F320 x 55 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: round | Shielding Angle: |



| LUMINANCE cd/(m2) | | |
|-------------------|--------|---------|
| G (DEG) | C0/180 | C90/270 |
| 85 | 10843 | 11109 |
| 80 | 9371 | 9434 |
| 75 | 9479 | 9473 |
| 70 | 9789 | 9761 |
| 65 | 10065 | 10028 |
| 60 | 10305 | 10265 |
| 55 | 10520 | 10479 |
| 50 | 10708 | 10664 |
| 45 | 10876 | 10829 |


C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 01 February 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.340m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

| | | |
|-----------------------------|-----------------|------------------|
| NAME: 95EL401524W/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: F320 x 55 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: round | Shielding Angle: |

| pcc | 80% | | | 70% | | | 50% | | | 30% | | | 10% | | | 0 |
|-----|-----------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|---|
| pw | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 0 |
| pfc | 20% | | | 20% | | | 20% | | | 20% | | | 20% | | | 0 |
| RCR | RCR:Room Cavity Ratio | | | | | | | | | | | | | | | |



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:01 February 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

WEC AND CCEC

| | | |
|-----------------------------|-----------------|------------------|
| NAME: 95EL401524W/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: F320 x 55 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: round | Shielding Angle: |

| pcc | 80% | | | 70% | | | 50% | | | 30% | | | 10% | | | 0 |
|------|-----------------------|------|------|------|------|------|----------------------------------|------|------|------|------|------|------|------|------|---|
| pw | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 0 |
| pfc | 20% | | | 20% | | | 20% | | | 20% | | | 20% | | | 0 |
| RCR | RCR:Room Cavity Ratio | | | | | | Wall Exitance Coefficients (WEC) | | | | | | | | | |
| 0.0 | | | | | | | | | | | | | | | | |
| 1.0 | .400 | .227 | .072 | .391 | .223 | .071 | .375 | .215 | .069 | .360 | .208 | .067 | .346 | .201 | .065 | |
| 2.0 | .369 | .202 | .062 | .361 | .199 | .061 | .347 | .193 | .060 | .333 | .187 | .059 | .321 | .182 | .057 | |
| 3.0 | .338 | .180 | .054 | .331 | .177 | .053 | .318 | .173 | .052 | .307 | .168 | .052 | .296 | .164 | .051 | |
| 4.0 | .310 | .161 | .047 | .304 | .159 | .047 | .293 | .155 | .046 | .282 | .152 | .046 | .272 | .148 | .045 | |
| 5.0 | .285 | .145 | .042 | .280 | .144 | .042 | .270 | .141 | .041 | .261 | .138 | .041 | .252 | .135 | .040 | |
| 6.0 | .264 | .132 | .038 | .259 | .131 | .038 | .250 | .128 | .037 | .242 | .126 | .037 | .234 | .123 | .037 | |
| 7.0 | .245 | .121 | .034 | .241 | .120 | .034 | .233 | .118 | .034 | .225 | .116 | .034 | .219 | .114 | .033 | |
| 8.0 | .228 | .112 | .031 | .225 | .111 | .031 | .218 | .109 | .031 | .211 | .107 | .031 | .205 | .105 | .031 | |
| 9.0 | .214 | .103 | .029 | .211 | .103 | .029 | .204 | .101 | .029 | .198 | .099 | .028 | .192 | .098 | .028 | |
| 10.0 | .201 | .096 | .027 | .198 | .096 | .027 | .192 | .094 | .027 | .187 | .093 | .026 | .182 | .091 | .026 | |

| pcc | 80% | | | 70% | | | 50% | | | 30% | | | 10% | | | 0 |
|------|-----------------------|------|------|------|------|------|---|------|------|------|------|------|------|------|------|---|
| pw | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 0 |
| pfc | 20% | | | 20% | | | 20% | | | 20% | | | 20% | | | 0 |
| RCR | RCR:Room Cavity Ratio | | | | | | Ceiling Cavity Exitance Coefficients (CCEC) | | | | | | | | | |
| 0.0 | .232 | .232 | .232 | .198 | .198 | .198 | .135 | .135 | .135 | .078 | .078 | .078 | .025 | .025 | .025 | |
| 1.0 | .221 | .190 | .162 | .189 | .163 | .139 | .129 | .112 | .096 | .074 | .065 | .056 | .024 | .021 | .018 | |
| 2.0 | .212 | .161 | .118 | .181 | .138 | .102 | .124 | .096 | .071 | .072 | .056 | .042 | .023 | .018 | .014 | |
| 3.0 | .202 | .139 | .089 | .173 | .120 | .077 | .119 | .083 | .054 | .069 | .049 | .032 | .022 | .016 | .010 | |
| 4.0 | .193 | .123 | .070 | .165 | .106 | .061 | .114 | .074 | .043 | .066 | .043 | .025 | .021 | .014 | .008 | |
| 5.0 | .183 | .110 | .057 | .157 | .096 | .049 | .108 | .067 | .035 | .063 | .039 | .021 | .020 | .013 | .007 | |
| 6.0 | .174 | .100 | .047 | .150 | .087 | .041 | .103 | .061 | .029 | .060 | .036 | .017 | .019 | .012 | .006 | |
| 7.0 | .166 | .092 | .040 | .143 | .080 | .035 | .099 | .056 | .025 | .057 | .033 | .015 | .019 | .011 | .005 | |
| 8.0 | .158 | .085 | .035 | .136 | .074 | .030 | .094 | .052 | .021 | .055 | .030 | .013 | .018 | .010 | .004 | |
| 9.0 | .150 | .079 | .030 | .130 | .068 | .027 | .090 | .048 | .019 | .052 | .028 | .011 | .017 | .009 | .004 | |
| 10.0 | .143 | .074 | .027 | .124 | .064 | .024 | .086 | .045 | .017 | .050 | .027 | .010 | .016 | .009 | .003 | |

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:01 February 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

| | | | | | | | | | | | |
|---|---------------|------------------|------|------|-----------------|---------------|----------------|------------------|------|------|------|
| NAME: 95EL401524W/GR | | | | | TYPE: | | | WEIGHT: 1 | | | |
| SPEC.: | | | | | DIM.: F320 x 55 | | | SERIAL No.: 0 | | | |
| MFR.: Elmark Industries JSC | | | | | SUR.: round | | | Shielding Angle: | | | |
| ceiling/cavity | 0.7 | 0.7 | 0.5 | 0.5 | 0.3 | 0.7 | 0.7 | 0.5 | 0.5 | 0.3 | |
| walls | 0.5 | 0.3 | 0.5 | 0.3 | 0.3 | 0.5 | 0.3 | 0.5 | 0.3 | 0.3 | |
| working plane | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | |
| Room dimensions | | Viewed crosswise | | | | | Viewed endwise | | | | |
| x = 2H y = 2H | 18.7 | 20.2 | 19.0 | 20.4 | 20.7 | 18.7 | 20.2 | 18.9 | 20.4 | 20.6 | |
| | 20.3 | 21.7 | 20.6 | 22.0 | 22.2 | 20.3 | 21.7 | 20.6 | 22.0 | 22.2 | |
| | 21.0 | 22.4 | 21.3 | 22.6 | 22.9 | 21.0 | 22.4 | 21.3 | 22.6 | 22.9 | |
| | 21.6 | 22.9 | 21.9 | 23.1 | 23.4 | 21.5 | 22.8 | 21.9 | 23.1 | 23.4 | |
| | 21.8 | 23.0 | 22.1 | 23.3 | 23.6 | 21.8 | 23.0 | 22.1 | 23.3 | 23.6 | |
| | 22.0 | 23.2 | 22.3 | 23.5 | 23.8 | 22.0 | 23.2 | 22.3 | 23.5 | 23.8 | |
| 4H | 2H | 19.3 | 20.7 | 19.6 | 20.9 | 21.2 | 19.3 | 20.7 | 19.6 | 20.9 | 21.2 |
| | 3H | 21.1 | 22.3 | 21.5 | 22.6 | 22.9 | 21.1 | 22.3 | 21.5 | 22.6 | 22.9 |
| | 4H | 22.0 | 23.1 | 22.3 | 23.4 | 23.7 | 21.9 | 23.0 | 22.3 | 23.4 | 23.7 |
| | 6H | 22.7 | 23.6 | 23.1 | 24.0 | 24.4 | 22.7 | 23.6 | 23.1 | 24.0 | 24.4 |
| | 8H | 23.0 | 23.9 | 23.4 | 24.2 | 24.6 | 23.0 | 23.9 | 23.4 | 24.2 | 24.6 |
| | 12H | 23.2 | 24.1 | 23.7 | 24.5 | 24.9 | 23.2 | 24.1 | 23.7 | 24.5 | 24.9 |
| 8H | 4H | 22.3 | 23.2 | 22.7 | 23.6 | 23.9 | 22.3 | 23.2 | 22.7 | 23.5 | 23.9 |
| | 6H | 23.2 | 23.9 | 23.6 | 24.3 | 24.8 | 23.2 | 23.9 | 23.6 | 24.3 | 24.8 |
| | 8H | 23.6 | 24.3 | 24.0 | 24.7 | 25.1 | 23.6 | 24.3 | 24.0 | 24.7 | 25.1 |
| | 12H | 24.0 | 24.6 | 24.4 | 25.0 | 25.5 | 24.0 | 24.6 | 24.5 | 25.0 | 25.5 |
| 12H | 4H | 22.3 | 23.1 | 22.7 | 23.5 | 23.9 | 22.3 | 23.1 | 22.7 | 23.5 | 23.9 |
| | 6H | 23.3 | 23.9 | 23.7 | 24.4 | 24.8 | 23.2 | 23.9 | 23.7 | 24.4 | 24.8 |
| | 8H | 23.7 | 24.3 | 24.2 | 24.8 | 25.2 | 23.7 | 24.3 | 24.2 | 24.8 | 25.2 |
| Variations with the observer position at spacings(CIE Pub.117): | | | | | | | | | | | |
| S = 1.0H | + 0.1 / - 0.2 | | | | | + 0.1 / - 0.2 | | | | | |
| 1.5H | + 0.2 / - 0.3 | | | | | + 0.2 / - 0.3 | | | | | |
| 2.0H | + 0.1 / - 0.3 | | | | | + 0.1 / - 0.3 | | | | | |

CIE Pub.117, 1920 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 2.3)
Area: 0.06831 m2

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:01 February 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

| | | |
|-----------------------------|-----------------|------------------|
| NAME: 95EL401524W/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: F320 x 55 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: round | Shielding Angle: |


| REFLECTANCE | | | | | | | | | | |
|----------------------------------|--|-----|-----------|-----|-----|-----|-----|---------------|-----|--------|
| Ceiling | 0.8 | 0.8 | 0.8 | 0.7 | 0.7 | 0.7 | 0.5 | 0.5 | 0.5 | 0 |
| Walls | 0.7 | 0.5 | 0.3 | 0.7 | 0.5 | 0.3 | 0.7 | 0.5 | 0.3 | 0 |
| Working plane | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0 |
| ROOM INDEX | UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$ | | | | | | | | | |
| $k = 0.60$ | 69 | 55 | 46 | 68 | 54 | 46 | 67 | 54 | 46 | 38 |
| 0.80 | 81 | 67 | 58 | 80 | 66 | 57 | 78 | 65 | 57 | 48 |
| 1.00 | 91 | 77 | 68 | 90 | 77 | 68 | 87 | 79 | 67 | 58 |
| 1.25 | 100 | 87 | 78 | 98 | 86 | 77 | 95 | 84 | 76 | 67 |
| 1.50 | 106 | 94 | 85 | 104 | 92 | 84 | 100 | 90 | 83 | 73 |
| 2.00 | 114 | 104 | 95 | 112 | 102 | 94 | 108 | 99 | 93 | 83 |
| 2.50 | 119 | 109 | 102 | 117 | 108 | 101 | 112 | 104 | 98 | 88 |
| 3.00 | 123 | 115 | 108 | 121 | 113 | 106 | 116 | 109 | 104 | 93 |
| 4.00 | 128 | 121 | 115 | 125 | 119 | 113 | 120 | 115 | 110 | 99 |
| 5.00 | 131 | 125 | 120 | 128 | 123 | 118 | 123 | 118 | 114 | 103 |
| ROOM INDEX | UF(total) | | | | | | | | | Direct |
| According to DIN EN 13032-2 2004 | | | Suspended | | | | | SHRNOM = 1.25 | | |

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature: 25.3°C
Operators:
Test Date: 01 February 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.340m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

| | | |
|-----------------------------|-----------------|------------------|
| NAME: 95EL401524W/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: F320 x 55 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: round | Shielding Angle: |




C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 01 February 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.340m [K=1.0000]
 Remarks:

AAI Figure

| | | |
|-----------------------------|-----------------|------------------|
| NAME: 95EL401524W/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: F320 x 55 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: round | Shielding Angle: |




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature:25.3°C
 Operators:
 Test Date:01 February 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.340m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

| | | |
|-----------------------------|-----------------|------------------|
| NAME: 95EL401524W/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: F320 x 55 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: round | Shielding Angle: |



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature: 25.3°C
Operators:
Test Date: 01 February 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.340m [K=1.0000]
Remarks:

LED Avg.L Report

| | | |
|-----------------------------|-----------------|------------------|
| NAME: 95EL401524W/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: F320 x 55 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: round | Shielding Angle: |


| AvgL | cd/m2 |
|------------------|-------|
| L_0~180 (65) av | 10249 |
| L_0~180 (75) av | 9762 |
| L_0~180 (85) av | 11425 |
| L_90~270 (65) av | 10169 |
| L_90~270 (75) av | 9671 |
| L_90~270 (85) av | 11332 |
| L_45 (65) av | 10207 |
| L_45 (75) av | 9725 |
| L_45 (85) av | 11371 |

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:01 February 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 01 February 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.340m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```