

ELMARK[®]

The Brand of Electricity

96GRFLED



TECHNICAL SPECIFICATION

LED GARDEN

ELMARK[®]

The Brand of Electricity

Technical data:

- Nominal voltage: 230V; 50-60Hz
- Power of the light source: 2W, 5W
- LED driver: mounted in the body
- Light source: SMD 2835
- Colour temperature: 3000-4000K
- Body: Aluminium
- Body Colour: Black
- Colour rendering index: Ra≥80
- Switch on/off: > 20 000
- Long life: 30 000h
- Dust and humidity protection level: IP65
- Type Installation: Recessed mounting

Features:

- Low power consumption
- Repeated switch on/off does not affect the lifespan of the fixture
- Instant light with maximum luminous flux
- Environmentally friendly - no mercury and lead
- No ultraviolet and infrared rays
- Resistant to shock and vibration stable body
- Low heat emission
- Compact size

Area of application:

- Outdoor Residential Areas
- Parks
- Gardens, Pools
- Walkways & Passages
- Fountains, Lawns, Entrance, Patio or Terrace and similar environments.

TECHNICAL SPECIFICATION

LED GARDEN

ELMARK[®]

The Brand of Electricity

Basic data:

| Model | Watt | Whole fixture lumens (lm) | Colour temp. (K) | Colour body | Length (mm) | Height (mm) |
|---------------|------|---------------------------|------------------|-------------|-------------|-------------|
| | | | | | | |
| 96GRFLED011WW | 2W | 50lm | 3000 | black | 95 | 95 |
| 96GRFLED011 | 2W | 50lm | 4000 | black | 95 | 95 |
| 96GRFLED012WW | 2W | 50lm | 3000 | black | 65 | 100 |
| 96GRFLED012 | 2W | 50lm | 4000 | black | 65 | 100 |
| 96GRFLED013WW | 2W | 50lm | 3000 | black | 105 | 60 |
| 96GRFLED013 | 2W | 50lm | 4000 | black | 105 | 60 |
| 96GRFLED014WW | 5W | 70lm | 3000 | black | 200 | 60 |
| 96GRFLED014 | 5W | 70lm | 4000 | black | 200 | 60 |
| 96GRFLED015WW | 5W | 70lm | 3000 | black | 60 | 200 |
| 96GRFLED015 | 5W | 70lm | 4000 | black | 60 | 200 |

• EN 55015 • EN 61547 • EN 61000-3-2 • EN 60598-1 • EN 60598-2-2

